

# Portable Generators

*Portability. Durability. Performance. These are the words we attach to all Mi-T-M Outdoor equipment and our portable generators live up to the accolades. Built for tough jobs in tough environments, each delivers reliable electric backup, and are powerful enough for anything the outdoorsman can throw at them. Power your hunting cabin and campsite without worry, the built-in receptacles let you plug in directly with no adapter!*



**MOSSY OAK**  
BRAND CAMO

## Alternator

- Total harmonic distortion (THD) less than 6%
- Copper and aluminum windings

## Engine

- Mi-T-M OHV engine with low oil shutdown

## Frame

- Low profile, compact design
- Wraparound frame with 1-inch steel tubing

## Components

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Large low-tone mufflers
- Engine on/off switch
- Fuel shut-off valve
- DC charging/battery charging

## Miscellaneous

- Circuit breaker protected

## 3600-Watt Additional Features:

### Alternator

- Brushed 120V alternator

## 3600 & 6000-Watt Additional

### Features:

### Engine

- Recoil starting system

## Warranties

**1 Year** Alternator     **1 Year** Mi-T-M Engine



GEN-3600-ODMO



GEN-6000-ODMO



GEN-8000-ODME

## 6000 & 8000-Watt Additional Features:

### Alternator

- Brushed 120V/240V alternator

### Engine

- Automatic idle control

### Frame

- Wheel kit with tires and rubber gripped handles

## 8000-Watt Additional Features:

### Engine

- Electric start (battery included)

- RV Generator Adapter available for all models (order part #32-0915)
- 30A/125V Female/Male; used to connect RV cord sets to 30A generators


Model Number	GEN-3600-ODMO	GEN-6000-ODMO	GEN-8000-ODME
Max. AC Output	3600 watts	6000 watts	8000 watts
Rated AC Output	3000 watts	5500 watts	7000 watts
Displacement/Engine	212cc Mi-T-M OHV	389cc Mi-T-M OHV	402cc Mi-T-M OHV
Frequency/Voltage	Brushed 120V,60Hz	Brushed 120V/240V,60Hz	Brushed 120V/240V,60Hz
Max. Amps (120V)	30.0	50.0/25.0	66.6/33.3
Cont. Amps (120V)	25.0	45.8/22.9	58.3/29.2
Receptacle	(2) 120V 20A GFCI duplex (1) 120V 30A twist lock	(2) 120V 20A GFCI duplex (1) 120V 30A twist lock (1) 120V/240V, 30A twist lock	(2) 120V 20A GFCI duplex (1) 120V 30A twist lock (1) 120V/240V, 30A twist lock
Main Circuit Breaker	(1) Main circuit breaker (2) 20A circuit breaker, single pole (1) 10A DC breaker	(1) Main circuit breaker (2) 20A circuit breaker, single pole (1) 10A DC breaker	(1) Main circuit breaker (2) 20A circuit breaker, single pole (1) 10A DC breaker
Rated Speed	3600 RPM	3600 RPM	3600 RPM
Fuel Capacity	4 gallons	6.6 gallons	6.6 gallons
Run Time (at full load)	8.5 hours	6.5 hours	6.0 hours
Dimensions (LxWxH)	24.88in. x 17.64in. x 17.96in.	39.1in. x 28.67in. x 30.65in.	39.1in. x 28.67in. x 30.65in.
Ship Wt.	134 lb.	228 lb.	237 lb.
Net Wt.	102 lb.	180 lb.	195 lb.



NEMA L14-30R  
120/240V



NEMA L5-30R  
120VAC



GFCI 5-20R



CSA  
CERTIFIED

\*Dimensions include the wheel kit with the handles in the down position.

Models are compliant in 50 states.